

ONESEAL PTW 5.0 CABLE SEAL

A PULL TO TIGHTEN CABLE SEAL - WITH Ø5
MM (3/16) CABLE AND WINDOW PROTECTION
COVER

A high security pull-tight cable seal designed for demanding transport and logistics applications. The OneSeal PTW5 combines flexible cable sealing with strong tamper evidence and practical handling across a wide range of sealing points.

The cable



Flexible galvanized steel cable with high tensile strength. The Ø5 mm cable is non-preformed. Standard length 350 mm - other lengths available on request.

Fits any container, truck or trailer.

The locking cylinder

The metal body features a non-flammable shock proof plastic cover and a transparent plastic shield, protecting the engraving against tampering. Standard color is white. Other colors are available on request.

Certificates

ISO 17712:2013 (H) and C-TPAT compliant.

OneSeal is ISO 9001:2015 compliant.



Laser engraving

Unique serial number and marking of choice will be engraved by use of high technology laser engraving which prevents tampering. All seals are engraved with consecutive unique numbering. Barcoding can also be applied.

Packing

The seals are packed in two pieces – cylinders and cables. The cylinders are packed on tape in numerical order. 200 seals per box.

Weight and dimensions

	Weight	Length	Width	Height
200 pcs. box	13 kg	43 cm	21 cm	10 cm

GET IN TOUCH

OneSeal ApS
+45 4914 8800

oneseal@oneseal.com
www.oneseal.com

Vibe Allé 2
2980 Kokkedal, Denmark